

THUNDERHEAD®

THUNDERHEAD 85/100 & 125GR.

1. Slide rings about 1/8" toward the threads. Push ferrule firmly into the safety wrench, ferrule will stay in place by itself. With free hand, place blades into slot, slide forward until blade tip seats under the point.
2. Continue to hold head with wrench, screw shaft onto head.
3. N.A.P. UBARs (Universal Broadhead Adapter Rings) MUST be used when using carbon or small diameter aluminum shafts.

THUNDERHEAD EDGE

1. Mount the broadhead in the safety wrench provided.
2. Remove the two retaining screws with small screwdriver.
3. Carefully remove the dull/old blade. Insert new blade, insert the screws and re-tighten.
4. Repeat for other two blades. Reposition head in the wrench if needed.
5. Dispose of old blades properly and HUNT!

HANDLE WITH EXTREME CAUTION

This product may be extremely dangerous and will cause injury if handled improperly. To avoid injury use the enclosed safety wrench when attaching and removing broadhead. Store heads in quiver after assembly.

NEW ARCHERY PRODUCTS CORP. PRODUCTS ARE PATENTED OR LICENCED BY ONE OR MORE OF THE FOLLOWING U.S. PATENTS. OTHER PATENTS PENDING.

7165543	7338397	6939258	7074143	6910472
6213114	6431162	7047959	7331338	6958023
6684874	6915791	7232390	6142896	6494196
6913008	7037222	6186135	6782881	7025697
5016602	6634349	6942551	6102020	6398676
6089216	6290903	6050251	6258000	6044832
6174252	5743245	5941784	5722381	5871410
5526799	5564713	7331338		

